



SLIP METER RISERS

FEATURES:

- ***DESIGNED TO ALLOW FASTER AND EASIER UNDERGROUND SERVICE ENTRANCE INSTALLATIONS.***
- ***PROVIDES CABLE PROTECTION FROM GROUND MOVEMENT.***

Slip Meter Risers

Carlton offers a full line of slip meter risers for use in electrical service entrance applications. The product line provides solutions for applications requiring a non-rigid connection, with incoming service conduit diameters ranging from 2" to 4".



Part #	Description	Length A	Inside Diameter B (Minimum)	Thread Length C	Thread Size	Carton Quantity	Case Weight (Lbs)
E954JXX	2" slip joint	24.00 (609.6)	2.750 (69.85)	0.825 (20.951)	2" NPT	20	43.6
E954LXX	3" slip joint	24.00 (609.6)	4.01 (101.85)	0.797 (20.24)	3" NPT	10	41.9
E954NXX	4" slip joint	24.00 (609.6)	5.06 (128.52)	0.773 (19.63)	4" NPSC	5	31.8

The slip meter risers are fitted with a terminal adapter for easy installation at the service entrance location. This product provides a low-cost method to comply with NEC 300-5 (j), which requires protection for buried cables in areas subject to ground movement due to frost or trench settling.